

SPECIFICATION		COLOR : BLACK,ORANGE,CLEAR,BLUE		
Polyurethane Tube		LENGTH	WORKING	WORKING
OD	ID	M/ROLL	TEMPERATOR	PRESSURE
4	2	100/200	0-60 °C / 32-140°F	0-150psi / 0-9.9kgf / cm <sup>2</sup> (0-990KPa)
4	2.5	100/200		
6	4	100/200		
8	5	100		
10	6.5	100		
12	8	100		



SPECIFICATION		COLOR : BLACK,ORANGE,CLEAR,BLUE		
Spiral air hose PU. Tube		LENGTH	WORKING	WORKING
OD	ID	M/ROLL	TEMPERATOR	PRESSURE
4	2.5	3M-25M	0-60 °C / 32-140°F	0-150psi / 0-9.9kgf / cm <sup>2</sup> (0-990KPa)
6	4	3M-25M		
8	6	3M-25M		
10	6.5	3M-25M		
12	8	3M-25M		



### การผลิต

- 1) ขนาด OD/ID ของสายลมที่ต้องการ เช่น 12x8mm , 10x6.5mm
- 2) Service Length หรือความยาวยืดใช้งานที่ต้องการ เช่นระยะยืดใช้งานที่ 4 เมตร, 2 เมตร
- 3) ความยาวหัวท้ายส่วนที่ไม่ขาด (หากต้องการความยาวพิเศษมากกว่าปกติ)
- 4) ระบุว่าต้องการ/ไม่ต้องการ Coupler (มีผลต่อราคา)

SPECIFICATION		COLOR : WHIT TRANSLUCENT		
PTFE TUBE (สายเทปลอน)		LENGTH	WORKING	WORKING
OD	ID	M/ROLL	TEMPERATOR	PRESSURE
4	2	100	-2.0 - 180°C	0-150psi / 0-9.9kgf / cm <sup>2</sup> (0-990KPa)
6	4	100		
8	6	100		
10	8	100		
12	10	50		
16	14	50		



SPECIFICATION		COLOR : Clear, Black, Green, Red, Blue, Yellow, Grey		
PA (Polyamide)		LENGTH	WORKING	WORKING
OD	ID	M/ROLL	TEMPERATOR	PRESSURE RANGE
4	2	100	-40°C – 100 °C	Vacuum up to 50Bar as per Diameter & Temp.
4	2.7	100		
5	3.3	100		
6	4	100		
8	6	100		
10	7.5	100		
10	8	100		
12	9	100		
12	10	100		
14	11	100		
14	12	100		
16	13	100		



SPECIFICATION		COLOR : BLACK,CLEAR		
NYLON		LENGTH	WORKING	WORKING
OD	ID	M/ROLL	TEMP	PRESSURE
4	2	200	0-60 °C / 32-140°F	0-150psi / 0-9.9kgf / cm <sup>2</sup> (0-990KPa)
4	2.5	200		
6	4	100		
6.35	4.5	100		
8	6	100		
9.5	7	100		
10	7.5	100		
12	9	100		
12.7	9.5	100		



SPECIFICATION		Working Temperature	Working Pressure Range
Tube	Male		
4	1/8	0-60 °C / 32-140°F	0-150psi 0-9.9kgf / cm <sup>2</sup> 0-990KPa
4	1/4		
4	3/8		
4	1/2		
6	1/8		
6	1/4		
6	3/8		
6	1/2		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/8		
10	1/4		
10	3/8		
10	1/2		
12	1/8		
12	1/4		
12	3/8		
12	1/2		



SPECIFICATION		Working Temperature	Working Pressure Range
HVFF			
Tube	Tube	0-60 °C / 32-140°F	0-150psi  0-9.9kgf / cm <sup>2</sup>  0-990KPa
4	4		
6	6		
8	8		
10	10		
12	12		



SPECIFICATION		Working Temperature	Working Pressure Range
HVSF			
Tube	Male	0-60 °C / 32-140°F	0-150psi  0-9.9kgf / cm <sup>2</sup>  0-990KPa
4	M5		
4	1/8		
4	1/4		
6	M5		
6	1/8		
6	1/4		
6	3/8		
6	1/2		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/8		
10	1/4		
10	3/8		
10	1/2		
12	1/8		
12	1/4		
12	3/8		
12	1/2		



SPECIFICATION		Working Temperature	Working Pressure Range
HVFS			
Tube	Male		
4	M5	0-60 °C / 32-140°F	0-150psi
4	1/8		
4	1/4		
6	M5		
6	1/8		
6	1/4		
6	3/8		0-9.9kgf / cm <sup>2</sup>
6	1/2		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/8		0-990KPa
10	1/4		
10	3/8		
10	1/2		
12	1/8		
12	1/4		
12	3/8		
12	1/2		



SPECIFICATION		Working Temperature	Working Pressure Range
PC			
Tube	Male	0-60 °C / 32-140°F	0-150psi  0-9.9kgf / cm <sup>2</sup>  0-990KPa
4	M5		
4	1/8		
4	1/4		
6	M5		
6	1/8		
6	1/4		
6	3/8		
6	1/2		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/8		
10	1/4		
10	3/8		
10	1/2		
12	1/4		
12	3/8		
12	1/2		



SPECIFICATION		Working Temperature	Working Pressure Range
PCF			
Tube	Female		
4	1/8	0-60 °C / 32-140°F	0-150psi 0-9.9kgf / cm <sup>2</sup> 0-990KPa
4	1/4		
6	1/8		
6	1/4		
6	3/8		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/8		
10	1/4		
10	3/8		
10	1/2		
12	1/4		
12	3/8		
12	1/2		



SPECIFICATION		Working Temperature	Working Pressure Range
PL			
Tube	Male	0-60 °C / 32-140°F	0-150psi  0-9.9kgf / cm <sup>2</sup>  0-990KPa
4	M5		
4	1/8		
4	1/4		
6	M5		
6	1/8		
6	1/4		
6	3/8		
6	1/2		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/8		
10	1/4		
10	3/8		
10	1/2		
12	1/4		
12	3/8		
12	1/2		





SPECIFICATION		Working Temperature	Working Pressure Range
PLF			
Tube	Male		
4	M5	0-60 °C / 32-140°F	0-150psi  0-9.9kgf / cm <sup>2</sup>  0-990KPa
4	1/8		
4	1/4		
6	M5		
6	1/8		
6	1/4		
6	3/8		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/8		
10	1/4		
10	3/8		
10	1/2		
12	1/4		
12	3/8		
12	1/2		



SPECIFICATION		Working Temperature	Working Pressure Range
PD			
Tube	Male	0-60 °C / 32-140°F	0-150psi  0-9.9kgf / cm <sup>2</sup>  0-990KPa
4	M5		
4	1/8		
4	1/4		
6	M5		
6	1/8		
6	1/4		
6	3/8		
6	1/2		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/8		
10	1/4		
10	3/8		
10	1/2		
12	1/4		
12	3/8		
12	1/2		



SPECIFICATION		Working Temperature	Working Pressure Range
PB			
Tube	Male		
4	M5	0-60 °C / 32-140°F	0-150psi 0-9.9kgf / cm <sup>2</sup> 0-990KPa
4	1/8		
4	1/4		
6	M5		
6	1/8		
6	1/4		
6	3/8		
6	1/2		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/8		
10	1/4		
10	3/8		
10	1/2		
12	1/4		
12	3/8		
12	1/2		



SPECIFICATION		Working Temperature	Working Pressure Range
PX			
Tube	Male		
4	M5	0-60 °C / 32-140°F	0-150psi  0-9.9kgf / cm <sup>2</sup>  0-990KPa
4	1/8		
4	1/4		
6	M5		
6	1/8		
6	1/4		
6	3/8		
6	1/2		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/8		
10	1/4		
10	3/8		
10	1/2		
12	1/4		
12	3/8		
12	1/2		



SPECIFICATION		Working Temperature	Working Pressure Range
PHF			
Tube	Male	0-60 °C / 32-140°F	0-150psi 0-9.9kgf / cm <sup>2</sup> 0-990KPa
4	M5		
4	1/8		
4	1/4		
6	M5		
6	1/8		
6	1/4		
6	3/8		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/4		
10	3/8		
10	1/2		
12	1/4		
12	3/8		
12	1/2		



SPECIFICATION		Working Temperature	Working Pressure Range
PH			
Tube	Male	0-60 °C / 32-140°F	0-150psi  0-9.9kgf / cm <sup>2</sup>  0-990KPa
4	M5		
4	1/8		
4	1/4		
6	M5		
6	1/8		
6	1/4		
6	3/8		
8	1/8		
8	1/4		
8	3/8		
8	1/2		
10	1/4		
10	3/8		
10	1/2		
12	1/4		
12	3/8		
12	1/2		



**SPECIFICATION**

<b>PE Tube</b>	<b>Working Temperature</b>	<b>Working Pressure Range</b>
4	0-60 °C	0-150psi 0-9.9kgf / cm <sup>2</sup> 0-990KPa
6		
8		
10		
12		

**SPECIFICATION**

<b>PV Tube</b>	<b>Working Temperature</b>	<b>Working Pressure Range</b>
4	0-60 °C	0-150psi 0-9.9kgf / cm <sup>2</sup> 0-990KPa
6		
8		
10		
12		



**SPECIFICATION**

<b>PU Tube</b>	<b>Working Temperature</b>	<b>Working Pressure Range</b>
4	<b>0-60 °C</b>	<b>0-150psi 0-9.9kgf / cm<sup>2</sup> 0-990KPa</b>
6		
8		
10		
12		

**SPECIFICATION**

<b>PY Tube</b>	<b>Working Temperature</b>	<b>Working Pressure Range</b>
4	<b>0-60 °C</b>	<b>0-150psi 0-9.9kgf / cm<sup>2</sup> 0-990KPa</b>
6		
8		
10		
12		





SPECIFICATION			
PG		Working Temperature	Working Pressure Range
Tube D1	Tube D2		
6	4	0-60 °C	0-150psi
8	6		0-9.9kgf / cm <sup>2</sup>
10	8		0-990KPa
12	10		



SPECIFICATION			
PW		Working Temperature	Working Pressure Range
Tube D1	Tube D2		
6	4	0-60 °C	0-150psi
8	6		0-9.9kgf / cm <sup>2</sup>
10	8		0-990KPa
12	10		



SPECIFICATION		
SILENCER	Working Temperature	Working Pressure Range
Male	0-60 °C	0-150psi 0-9.9kgf / cm <sup>2</sup> 0-990KPa
M5		
1/8		
1/4		
3/8		
1/2		
3/4		



SPECIFICATION			
SOCKET		Working Temperature	Working Pressure Range
CODE	MALE	0-60 °C / 32-140°F	0-150psi / 0-9.9kgf / cm <sup>2</sup> (0-990KPa)
SM-10	1/8"		
SM-20	1/4"		
SM-30	3/8"		
SM-40	1/2"		
ONE TOUCH OR TWO TOUCH			



**ONE TOUCH**



SPECIFICATION			
SOCKET		Working Temperature	Working Pressure Range
CODE	FEMALE	<b>0-60 °C / 32-140°F</b>	<b>0-150psi / 0-9.9kgf / cm<sup>2</sup> (0-990KPa)</b>
SF-10	1/8"		
SF-20	1/4"		
SF-30	3/8"		
SF-40	1/2"		
<b>ONE TOUCH OR TWO TOUCH</b>			



SPECIFICATION			
SOCKET		Working Temperature	Working Pressure Range
CODE	LOCK TUBE	<b>0-60 °C / 32-140°F</b>	<b>0-150psi / 0-9.9kgf / cm<sup>2</sup> (0-990KPa)</b>
SP-10	1/8"		
SP-20	1/4"		
SP-30	3/8"		
SP-40	1/2"		
<b>ONE TOUCH OR TWO TOUCH</b>			



SPECIFICATION			
SOCKET		Working Temperature	Working Pressure Range
CODE	HOSE	<b>0-60 °C / 32-140°F</b>	<b>0-150psi / 0-9.9kgf / cm<sup>2</sup> (0-990KPa)</b>
SH-10	1/8"		
SH-20	1/4"		
SH-30	3/8"		
SH-40	1/2"		
<b>ONE TOUCH OR TWO TOUCH</b>			



SPECIFICATION		Working Temperature	Working Pressure Range
PLUG			
CODE	MALE	<b>0-60 °C / 32-140°F</b>	<b>0-150psi / 0-9.9kgf / cm<sup>2</sup> (0-990KPa)</b>
PM-10	1/8"		
PM-20	1/4"		
PM-40	1/2"		



SPECIFICATION		Working Temperature	Working Pressure Range
PLUG			
CODE	FEMALE	<b>0-60 °C / 32-140°F</b>	<b>0-150psi / 0-9.9kgf / cm<sup>2</sup> (0-990KPa)</b>
PF-10	1/8"		
PF-20	1/4"		
PF-40	1/2"		



SPECIFICATION		Working Temperature	Working Pressure Range
PLUG			
CODE	LOCK TUBE	<b>0-60 °C / 32-140°F</b>	<b>0-150psi / 0-9.9kgf / cm<sup>2</sup> (0-990KPa)</b>
PP-10	1/8"		
PP-20	1/4"		
PP-40	1/2"		



SPECIFICATION			
PLUG		Working Temperature	Working Pressure Range
CODE	HOSE	<b>0-60 °C / 32-140°F</b>	<b>0-150psi / 0-9.9kgf / cm<sup>2</sup> (0-990KPa)</b>
PH-10	1/8"		
PH-20	1/4"		
PH-40	1/2"		

